

NEC



NEC LC19M

- LCD 19" Monitor (TN + TFT Film)
- Numerous adjustment options
- Integrated speakers
- Very thin and light

A High Quality Monitor
At An Affordable Price

www.nec-online.com

a division of NEC Computers International

SCREEN

Size	19 inches
Type	Active colour matrix TFT
Visibility angle	Horizontal 85° Vertical 85°
Inch per pixel	0,294 mm
Display zone	376,32mm x 301mm
Resolution	1280 x 1024 x 75 Hz
Number of colours	16, 7 million
Contrast ratio	800:1
Response time	20ms
Luminance	250 cd/m2
Backlight	4 CCFL (Cold Cathode light)

SCANNING FREQUENCY

Horizontal	31.5 kHz - 81 kHz
Vertical	55 kHz - 76 kHz

CONTROL OPTION

On Front	Power SW, exit Control (left/right), Adjustment (left/right), select, reset
OSD	Luminance, contrast, Auto Cont Auto adjustment, Position H, Position V, Size H, control colour, Language, position OSD, extinction OSD, lock OSD, Hot key, Resolution adjustment, Timer, Reset, Screen mode, Information
Order	VESA DDC2B

OTHER RESOLUTIONS

720 x 400 @ 70Hz
640 x 480 @ 60Hz/75Hz
800 x 600 @ 60Hz/75Hz
1024 x 768 @ 60Hz/70Hz/75Hz
1280 x 1024 @ 60Hz/75Hz

POWER

Voltage	AC 100-240V
On	< 60W
Stand by	<3W

AUDIO SYSTEM

Speakers	1W + 1W
----------	---------

ENTRY SIGNAL

Video	Analogical RGB
Connectors	Mini D-sub 15 pins
Cable	1,80m

ERGONOMICS, SECURITY, CERTIFICATION

Security	UL 1950 (UL), CSA C22.2 No.950 (C-UL) CE Marketing, TUV-GS (EN60950) Kensington Lock
EMC	FCC-B, DOC-B, EN55022-B, EN61000-3-2,-3-3 EN55024 (IEC6100-4-2,-4-3,-4-4,-4-5, - 4-6,-4-8,-4,11)
VLF/ELF	MPR-II, TCO 03
Power	EPA, TCO 03
Ergonomy	MPR-II, TCO 03, ISO 13406-2, Energy Star
Plug and Play	DPMS, VESA DDC 1/2B

CONDITIONS OF USE

Temperature	0-50°C
Humidity	8-95% (without condensation)
Altitude	0-3000m

Dimensions (W x H x D)

Screen	425 x 420 x 210 mm
Weight	4.8 kg
Packaging Inc	485 x 527 x 140 mm
Weight (packaging Inc)	5.8 kg

NEC LC19M

**A High Quality Monitor
At An Affordable Price**



Visit us on www.nec-online.com